



Duravit No.1 Handrinse basin # 07453600412

| < 360 mm > |



Handrinse basin	Dimension	Weight	Order number
without overflow, with tap platform, tap hole on right side, fixings included, underneath glazed, 360 mm			
Colors			
00 White Alpin			
Variant			
●	360 x 220 mm	6.700 kilogram	07453600412
Infobox			
Mandatory in combination with a bottle trap inclusive extended pipe			
Accessory			
Slotted waste for washbasins without overflow	75 mm	0.400 kilogram	005038
Recommended faucets			
Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,			B21010001
Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,			B11010002
Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,			B11010001
Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,			B21010002

Single lever basin mixer S ceramic cartridge, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	DE1010001
Single lever basin mixer S ceramic cartridge, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	DE1010002
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	DE1011001
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	DE1011002
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, projection 100 mm, flexible connection hoses 3/8", flow rate 4,5 l/min (3 bar), normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11011001
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, projection 100 mm, flexible connection hoses 3/8", flow rate 4,5 l/min (3 bar), normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11011002
Single lever basin mixer S MinusFlow ceramic cartridge, projection 100 mm, flexible connection hoses 3/8", flow rate 3,5 l/min (3 bar), normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11012001
Single lever basin mixer S MinusFlow ceramic cartridge, projection 100 mm, flexible connection hoses 3/8", flow rate 3,5 l/min (3 bar), normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11012002
Single lever basin mixer M ceramic cartridge, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11020002
Single lever basin mixer M FreshStart ceramic cartridge, in centre position cold water, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11021001
Single lever basin mixer M FreshStart ceramic cartridge, in centre position cold water, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11021002

Single lever basin mixer M MinusFlow ceramic cartridge, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 3,5 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11022001
Single lever basin mixer M MinusFlow ceramic cartridge, projection 106 mm, flexible connection hoses 3/8", normal spray, flow rate 3,5 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11022002
Single lever basin mixer S FreshStart ceramic cartridge, projection 110 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	TU1011001
Single lever basin mixer S FreshStart ceramic cartridge, projection 110 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	TU1011002
Single lever basin mixer S ceramic cartridge, projection 110 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	TU1010001
Single lever basin mixer S ceramic cartridge, projection 110 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	TU1010002
Single lever basin mixer S ceramic cartridge, projection 100 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11010001
Single lever basin mixer S ceramic cartridge, projection 100 mm, flexible connection hoses 3/8", flow rate 5,0 l/min (3 bar), normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11010002

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.