



Geberit Duofix element for bidet, 82 cm, universal



APPLICATION PURPOSES

- For drywall construction
- For installation in part-height prewall installations
- For installation in part-height Geberit Duofix system walls
- For wall-hung bidets with deck-mounted tap
- For floor constructions 0–20 cm

CHARACTERISTICS

- Statically self-supporting frame, protected against corrosion with powder coating

- Frame with $\varnothing 9$ mm drilling holes for fastening in wood frame construction
- Galvanized feet
- Feet adjustable 0–20 cm
- Non-slip leg supports
- Foot plate depth suitable for installation in U-profiles UW 50 and UW75 and Geberit Duofix system rails
- Rotatable foot plates
- Fastening distance for wall-hung bidet 18 or 23 cm
- Height-adjustable bidet fastening
- Fastening for connection bend, height-adjustable and sound-absorbing

- Tap attachments adjustable in width and height

TECHNICAL DATA

Product material	Steel
Height-adjustable	Yes

SCOPE OF DELIVERY

- Connection bend made of PE-HD, $\varnothing 50$ mm
- Seal $\varnothing 44 / 32$ mm
- 2 threaded rods M12
- Fastening material

Art. no.	B cm	H cm	T cm
111.524.00.1	50	82	10

Geberit Duofix element for bidet, 82 cm, universal

BATHROOM COLLECTIVE

Phone Number: (02) 9011-5711