



NEWPORT

CODE: BCNSS

NOTE: Height and reach can be adjusted to suit design requirements. Reach can be customised 300-700mm. Hot & cold 15mm BSP male threads required at 900mm off FFL. Rough-in template provided. Wall mounting on timber requires minimum 45mm depth timber blocking behind finished wall, down centre line of shower.

SHOWER ROSE:

Reach 450mm (centre to centre), adjustable 300mm to 700mm.
Natura 200mm diameter (as shown)
Height from centre of taps 1070mm

Daintree 250mm diameter (not shown)
Daintree 200mm diameter (available mid-2021)
Height from centre of taps 1040mm

SHOWER PIPE:

25mm dia with foot washer outlet
Overall height 1630mm
Overall depth including taps 155mm
Total height when installed 2200mm

SHOWER TAPS:

Tap width (centre to centre) 280mm, can be reduced to a minimum of 200mm if required
Available with all tap styles in our range.
Depth 155mm

WELS:

Newport wall mounted unit with Bundeena shower (Code BCCBS) Flow Rate: 9L/min. 3 Star rating WELS registration #SM13610

Newport wall mounted unit with Eden shower (Code BCCES) Flow Rate: 9L/min. 3 Star rating WELS registration #SM13614

BATHROOM COLLECTIVE

Phone Number: (02) 9011-5711

SCALE 1:10 at A4